



FCC TEST REPORT

For

Hibertek International Limited

Product Name:	All in One
Trademark:	N/A
Model Number:	T23 T22.
Prepared For :	Hibertek International Limited
Address :	Rm. 6, 21F., No.5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	A. Floor 3, 44 Building, Tanglang Industrial Park B, Taoyuan Street, Nanshan District, Shenzhen, China
Test Date:	Jun. 26 - Jul. 02, 2015
Date of Report :	Jul. 02, 2015
Report No.:	BCTC-150607512



TABLE OF CONTENTS

TEST REPORT DECLARATION	3
1. GENERAL INFORMATION	4
1.1. Report information.....	4
1.2. Measurement Uncertainty.....	4
1.3. Test Facility.....	4
1.4. Test Uncertainty.....	4
2. PRODUCT DESCRIPTION	5
2.1. EUT Description.....	5
2.2. Block Diagram of EUT Configuration.....	5
2.3. Test Conditions.....	5
3. TEST RESULTS SUMMARY	6
4. TEST EQUIPMENT USED	7
4.1. For Conducted Emission Test.....	7
4.2. For Radiated Emission Measurement.....	7
5. CONDUCTED EMISSION TEST	8
5.1. Block Diagram of Test Setup.....	8
5.2. Test Standard.....	8
5.3. Conducted Emission Limit (Class B).....	8
5.4. EUT Configuration on Test.....	8
5.5. Operating Condition of EUT.....	8
5.6. Test Procedure.....	9
5.7. Test Result.....	9
6. RADIATED EMISSION MEASUREMENT	12
6.1. Block Diagram of Test Setup.....	12
6.2. Test Standard.....	12
6.3. Radiated Emission Limit(Class B).....	12
6.4. EUT Configuration on Test.....	13
6.5. Test Procedure.....	13
6.6. Test Result.....	13
APPENDIX I (PHOTOS OF THE EUT)	16
APPENDIX II (TEST PHOTOS OF THE EUT)	21



TEST REPORT DECLARATION

Applicant : **Hibertek International Limited**
Address : Rm. 6, 21F., No.5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)
EUT Description : **All in One**
Model Number : **T23**

Test Standards:

FCC Part 15 B: 2014

The EUT described above is tested by US to determine the maximum emission levels emanating from the EUT, the maximum emission levels are compared to the FCC Part 15 B Subpart Class B limits.

The measurement results are contained in this test report and Shenzhen BCTC Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these measurements.

Also, this report shows that the EUT is to be technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen BCTC Technology Co., Ltd.

Date of Test: Jun. 26 - Jul. 02, 2015

Prepared by(Engineer): *Myssa Jua*

Reviewer(Quality Manager): *Sophie Lee*

Approved & Authorized Signer(Manager): *Casey Wang*





1. GENERAL INFORMATION

1.1. Report information

- 1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are applicable to the similar items. In addition, such results must not be used to indicate or imply that BCTC approves, recommends or endorses the manufacture, supplier or use of such product/equipment, or that BCTC in any way guarantees the later performance of the product/equipment.
- 1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BCTC therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.
- 1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third party can obtain a copy of this report through BCTC, unless the applicant has authorized BCTC in writing to do so.

1.2. Measurement Uncertainty

Available upon request.

1.3. Test Facility

Site Description
Name of Firm : Shenzhen BCTC Technology Co., Ltd.

Site Location : A. Floor 3, 44 Building, Tanglang Industrial Park B,
Taoyuan Street, Nanshan District, Shenzhen, China

1.4. Test Uncertainty

Conducted Emission Uncertainty = $\pm 2.66\text{dB}$
Radiated Emission Uncertainty = $\pm 4.15\text{dB}$




2. PRODUCT DESCRIPTION

2.1.EUT Description

Description : **All in One**
Applicant : **Hibertek International Limited**
Rm. 6, 21F., No.5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)
Manufacturer : **Hibertek International Limited**
Rm. 6, 21F., No.5, Sec. 3, New Taipei Blvd., Xinzhuang Dist., New Taipei City 242, Taiwan (R.O.C.)
Model Number : **T23**

2.2.Block Diagram of EUT Configuration



2.3.Test Conditions

Temperature: 23~25℃

Relative Humidity: 55~63 %



3. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	Test Results
Conducted disturbance	Pass
Radiated disturbance	Pass

Remark: "N/A" means "Not applicable."



4. TEST EQUIPMENT USED

4.1. For Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
2	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Aug. 25, 14	1 Year
3	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Aug. 25, 14	1 Year
4	Conical	Emtek	N/A	N/A	N/A	N/A
5	Voltage Probe	Schwarzbeck	TK9416	N/A	Aug. 25, 14	1 Year
6	Coaxial Switch	Anritsu	MP59B	6100214550	Aug. 25, 14	1 Year


4.2. For Radiated Emission Measurement

Anechoic Chamber

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Aug. 25, 14	1 Year
2	Test Receiver	Rohde&Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
3	Bilog Antenna	Schwarzbeck	VULB9163	142	Aug. 25, 14	1 Year
4	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Aug. 25, 14	1 Year
5	Cable	Schwarzbeck	AK9513	ACRX1	Aug. 25, 14	1 Year
6	Cable	Rosenberger	N/A	FR2RX2	Aug. 25, 14	1 Year
7	Cable	Schwarzbeck	AK9513	CRRX2	Aug. 25, 14	1 Year
8	Cable	Schwarzbeck	AK9513	CRRX2	Aug. 25, 14	1 Year
9	Single Phase Power Line Filter	MPE	23332C	N/A	Aug. 25, 14	1 Year
10	Single Phase Power Line Filter	MPE	23333C	N/A	Aug. 25, 14	1 Year
11	Signal Generator	HP	864A	3625U00573	Aug. 25, 14	1 Year

5. CONDUCTED EMISSION TEST

5.1. Block Diagram of Test Setup



(EUT: All in One)

5.2. Test Standard

FCC Part 15 B: 2014

5.3. Conducted Emission Limit (Class B)

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

5.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet Part 15 B requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

5.4.1. All in One

Model Number: T23

5.5. Operating Condition of EUT

5.5.1. Setup the EUT and simulators as shown in Section 5.1.

5.5.2. Turn on the power of all equipments.

5.5.3. Let the EUT work in test modes (EUT Working) and test it.



5.6. Test Procedure


The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESHS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

The bandwidth of the test receiver (R&S Test Receiver ESHS30) is set at 10KHz.

5.7. Test Result

PASS


Please refer to the following pages.



Site Chamber #1 Phase: L1 Temperature: 26

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.6860	43.47	10.13	53.60	56.00	-2.40	QP	
2		0.6860	32.49	10.13	42.62	46.00	-3.38	AVG	
3		0.8700	40.76	10.15	50.91	56.00	-5.09	QP	
4		0.8700	28.85	10.15	39.00	46.00	-7.00	AVG	
5		1.1940	37.44	10.17	47.61	56.00	-8.39	QP	
6		1.1940	19.68	10.17	29.85	46.00	-16.15	AVG	
7		1.2980	37.74	10.17	47.91	56.00	-8.09	QP	
8		1.2980	22.22	10.17	32.39	46.00	-13.61	AVG	
9		1.3740	39.35	10.17	49.52	56.00	-6.48	QP	
10		1.3740	27.26	10.17	37.43	46.00	-8.57	AVG	
11		1.4740	37.31	10.17	47.48	56.00	-8.52	QP	
12		1.4740	23.36	10.17	33.53	46.00	-12.47	AVG	

*:Maximum data x:Over limit !:over margin



Site Chamber #1

Phase: N

Temperature: 26


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1780	40.15	10.06	50.21	64.57	-14.36	QP	
2		0.1780	28.67	10.06	38.73	54.57	-15.84	AVG	
3		0.6940	41.79	10.13	51.92	56.00	-4.08	QP	
4	*	0.6940	34.26	10.13	44.39	46.00	-1.61	AVG	
5		1.3860	34.52	10.17	44.69	56.00	-11.31	QP	
6		1.3860	23.24	10.17	33.41	46.00	-12.59	AVG	
7		3.5100	29.89	10.17	40.06	56.00	-15.94	QP	
8		3.5100	17.02	10.17	27.19	46.00	-18.81	AVG	
9		15.7740	28.64	10.15	38.79	60.00	-21.21	QP	
10		15.7740	12.37	10.15	22.52	50.00	-27.48	AVG	
11		27.6980	28.60	10.21	38.81	60.00	-21.19	QP	
12		27.6980	12.84	10.21	23.05	50.00	-26.95	AVG	

*:Maximum data x:Over limit !:over margin

6. RADIATED EMISSION MEASUREMENT


6.1. Block Diagram of Test Setup

6.1.1. Block Diagram of connection between the EUT and the simulators



(EUT: All in One)

6.1.2. Anechoic Chamber Test Setup Diagram



6.2. Test Standard

FCC Part 15 B: 2014

6.3. Radiated Emission Limit(Class B)

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMITS (dB μ V/m)
30 ~ 88	3	40.0
88 ~ 216	3	43.5
216 ~ 960	3	46.0
960 ~ 1000	3	54.0

Note:(1) The smaller limit shall apply at the edge between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT or system.



6.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize Its emission characteristics in normal application.

Operating Condition of EUT

6.4.1.Setup the EUT as shown on Section 6.1

6.4.2.Turn on the power of all equipments.

6.4.3.Let the EUT work in test mode(EUT working) and measure it.

6.5.Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.


The bandwidth setting on the test receiver is 120 KHz.

The EUT is tested in Anechoic Chamber. The frequency range from 30MHz to 1000MHz is checked. All the test results are listed in Section 6.6.

6.6.Test Result

PASS

Please refer to the following pages.




Site 966 BCTC Chamber #1

Polarization: *Horizontal*

Temperature: 26

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	36.0007	31.98	-8.59	23.39	40.00	-16.61	QP			
2	53.8818	31.61	-10.93	20.68	40.00	-19.32	QP			
3	* 86.8068	43.32	-17.91	25.41	40.00	-14.59	QP			
4	243.3772	41.57	-14.40	27.17	46.00	-18.83	QP			
5	547.0977	35.23	-7.20	28.03	46.00	-17.97	QP			
6	578.6699	33.07	-6.32	26.75	46.00	-19.25	QP			

*:Maximum data x:Over limit !:over margin



Site 966 BCTC Chamber #1

Polarization: *Vertical*

Temperature: 26

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	*	39.2991	42.91	-8.82	34.09	40.00	-5.91	QP			
2		62.6507	37.26	-12.05	25.21	40.00	-14.79	QP			
3		86.5029	42.29	-17.96	24.33	40.00	-15.67	QP			
4		245.9509	41.28	-14.32	26.96	46.00	-19.04	QP			
5		251.1804	42.23	-14.18	28.05	46.00	-17.95	QP			
6		502.9395	33.56	-8.15	25.41	46.00	-20.59	QP			

*:Maximum data x:Over limit !:over margin



APPENDIX I (PHOTOS OF THE EUT)

EUT Photo 1




EUT Photo 2



EUT Photo 3



EUT Photo 4



EUT Photo 5



EUT Photo 6




EUT Photo 7





APPENDIX II (TEST PHOTOS OF THE EUT)



***** END OF REPORT *****